
CIA/OER/S-07567-75 ALAN GREENSPAN

JUN 75 01 OF 01



Western Europe and Japan: Substituting Coal for Oil

Summary

Consumption by power generating plants is one of the few areas where government policy decisions by IEA countries could significantly cut the demand for OPEC oil in the 1980s. The following tabulation, which covers the consumption of oil in thermal generating plants in Western European countries and Japan, provides a crude numerical illustration of potential oil savings.

7 77			1075	. 2/	mil	h/A
na Estan	nated consum	uption in	13/3	ره و د.		2) U

- 2. Estimated consumption in 1980 if
 -oil must take care of increased
 -demand for thermal-generated EP 5.5 mil b/d
- 3. Estimated consumption in 1980 if,
 as OECD projects, high oil
 prices encourage some increase
 in coal consumption -4.6 mil b/d
- 4. Estimated consumption in 1980 if strong OECD government support for coal production, consumption, and exports is added to the natural market forces

3.4 mil b/d

This tabulation is to be regarded only as a rough calculation since important assumptions had to be made about the consumption of electric power in 1980, the position of nuclear power in the energy mix, the role of natural gas, and the environmental policies in consuming countries. The potential for converting electric power plants in use this year is not great, on the order of 500,000 b/d in 2 years' time.

CIA/OER 24 June 1975

Trends in Coal Use by Utilities

Prior to the 1973 embargo, oil use in generating electricity grew rapidly while coal use declined. Coal consumption in Japan and Europe declined rapidly in the late 1960s and early 1970s primarily because of rising production costs and strong competition from oil. In six major European countries (West Germany, France, Italy, Netherlands, Belgium, and Luxembourg) oil use in generating plants more than doubled during 1968-1974, while coal use stagnated (Table I). Because industrial, commercial, and household use of coal plummeted during this period, overall coal consumption in these six countries fell by 30% from 3.7 million b/d to 2.7 million b/d (oil equivalent).

25X6A

25X6A

Ability to Convert Power Plants to Coal

Over the next year or two, coal consumption by West
European and Japanese electric power generating plants could
be increased by the equivalent of 400,000 - 500,000 b/d

(oil equivalent) if the coal was available and appropriate
governmental orders were given. Most of this rise could come

about through conversion of plants with dual fuel capability to coal, reconversion of coal plants that had been converted to oil over the past decade, and the shifting of load factors and fuel mixes in plants that use a mixture of oil and coal. Conversion of this amount would require an increase in Free World steam coal production of about 40,000,000 tons.

· Converting Plants with Dual Fuel Boilers

cases where the plants were designed with a dual fuel capability or have been converted from coal to oil in recent years. In the late 1960s, some coal fired plants were converted to oil, largely because of environmental considerations.

In these cases, conversion to coal is relatively simple and inexpensive. The major cost factor and difficulty in making such conversions usually is a lack of coal handling facilities, which may have been removed when the plant was converted to oil. In addition, facilities to offload and transport coal might also be necessary to convert inland power generating plants that previously depended on domestic coal.

Germany and Japan have the greatest scope for shifting to coal over the next year or two. In Germany, in excess of 100,000 b/d of capacity could be shifted. Because of the sharp drop in coal usage since 1968 in France and the low countries, a like amount probably could be converted in other West European countries.

25X6

25X6A

25X6A

Conversion of Single Fuel Boiler Plants

Conversion of larger amounts of oil fired capacity
would require substantially more time and investment. The
bulk of the oil fired plants constructed over the past
decade have been designed only for oil firing. In these
cases, conversion without sizeable efficiency losses would
require the installation of new boilers, as well as coal
handling facilities. Depending upon the lay-out of each
plant and the land available new boilers to accommodate coal
might be installed without taking the plant out of service.
Alternately -- in multiboiler plants -- the conversion could
be carried out in stages to maintain most of the capacity
on-line during conversion. In any event, conversion of these
plants would require in excess of 2 years per plant, and
conversion of a substantial number of plants would probably
require a decade or more.

New Plants

Conversion of oil fired plants currently under construction or planned appears to offer the best long-term opportunity to boost coal fired capacity in Western Europe



Government Policy in Western Europe and Japan

Governments in Western Europe and Japan are firmly committed to increasing the use of coal by power plants but are limited by available coal supplies. Because of the high costs involved, assured long-term supplies are necessary before conversion can take place on a significant scale. These governments already have taken steps to stem the decline in domestic coal output and are attempting to line up supplies of steam coal from the US, Australia, South Africa, Poland, and India.



25X6A

25X6A -

Western Europe

25X6A

West European countries are also committed to expanding coal consumption, but plans are generally less advanced than in Japan. Coal supply availability is a pressing

constraint. Domestic coal output is expected to level off, with little increase in output anticipated through 1980. Any major increase in coal consumption thus will come from supplies of imported steam coal.

Most major West European countries have made inquiries with US coal suppliers — in an attempt to arrange large long-term contracts — and have also been trying to increase their imports from Poland, South Africa, and Australia.

Italian utility companies were instrumental in providing the financing for a 9 million ton coal export facility in South Africa. Germany and France also have reportedly signed contracts for South African steam coal.

Western Europe: Oil and Coal Consumption in Generating Electricity 1

		Coal		
	millior tons coa	· · · · · · · · · · · · · · · · · · ·		
1966	62.4-	840	370	
1967	67.8	910	410	
1968	71.0	950	. 450	
1969	74.1	.990	560	
1970	. 68.1	. 91.0	690	
1.971	71.8	960	800	
1972	69.0	920	920	
1973	.68.4	. 91.0	1060	
1974 c	st 70:2	940	980	

^{1.} West Germany, France, Italy, Netherlands, Belgium, Luxembourg. In the remainder of Western Europe an estimated 700,000 b/d of oil are consumed by generating plants. Only in the UK does coal provide a major share of the fuel consumed.

Table II

Japan: Oil and Coal Consumption in Generating Electricity

•	Coa	Oil		
	million tons coal	thousand b/d oil equivalent	thousand b/d	
1966	23.4	310	250	
1967	26.1	350	360	
1968	26.0	350	430	
1969	24.3	330	580	
1970	18.8	250	720	
1971	13.9	190	790	
.1972	10.7	140	970	
1973	8.3	` iio	1150	
1974 est	8.7	120	990	
			· .v ·	

^{1.} Public utility data only. Industrial power plants used an estimated 150,000 b/d of oil to generate electricity in 1974.